

Steam cleaner for Jewelry



This machine is strong decontamination using high pressure steam degreasing properties, high pressure column injection, for cleaning surface dirt, work pieces/objects will be bright after washing. The machine uses all-stainless steel and it will be never rusty. Multiple advanced overheating protection, some key components are imported with high quality standard. With features of durable, reducing failures, safe production.

Main parameters:

Power: 2.5KW; Voltage: 220V, 50/60Hz;

External dimensions: 50 * 45 * 45 (cm)

Weight: 18kg

Instructions for use:

1. The safety valve: a protective role in uncontrolled hypertension.
2. The inlet: Please note that when adding water, please check if there is pressure, it should be recommended to add water without pressure.

3. Regulating valves: To adjust regulating nozzle pressure.
4. Air pressure gauge: To check pressure volume.
5. Heating light: When heating, lights on.
6. Power Switch: On/Off (Note: Please turn off the switch after work).
7. Foot pedal system: control nozzle work.
8. Foot switch function: Turn the power switch then control foot pedal, it's for safety operation.
9. The spray nozzle: spray high-pressure steam.
11. Observing water valve 1: please add water when the valve is opened, close the valve when working.
12. Observing water valve 2: please add water when the valve is opened, close the valve when working.
13. To watch the water level quartz tube: easy for viewing water volume (Note: the water level should not be less than the tube position of 1/3, not more than 1/3).
14. Water outlet valve: cylinder should be a regular cleaning monthly, can only operate this step without pressure.

Safety operation

1. Check the water level if it is enough before power turning on the power, check the valve if it is closed.
2. After adding sufficient distilled water, close No. 2, 11 and 12 valve then turn off the power switch.
3. The boot heating lights, the pressure rises about 10 minutes, after that the gauge indicates 7Kg, light will automatically shut off.
4. Turn on foot pedal to control nozzle system for work.
5. After the work is completed, please turn off the foot pedal and then turn off the device. Off steam if necessary.

Note: Please do not use the machine if gas leak out, please turn off the power and contact with the supplier